

| Name                            | Torque |       | Notes |
|---------------------------------|--------|-------|-------|
|                                 | Nm     | FtLbs |       |
| Axle nut, front                 | 81.3   | 60    | 3     |
| Axle nut, rear                  | 88.1   | 65    | 2     |
| Axle pinch bolts                | 23     | 17    | 3     |
| Brake caliper bolts             | 27     | 20    | 3     |
| Brake disc bolts                | 17.5   | 13    | 2     |
| Brake disc bolts (front)        | 14.8   | 11    | 2     |
| Brake hose banjo bolt           | 32.5   | 24    |       |
| Brake lever adjuster nut (rear) | 5.4    | 4     |       |
| Brake lever pivot bolt (rear)   | 29.7   | 22    | 2     |
| Brake reservoir cap bolt (rear) | 1.3    | 1     |       |
| Chain adjuster nut              | 27     | 20    |       |
| Chain guide bolts               | 6.7    | 5     | 3     |
| Chain roller bolt (TP/BT)       | 13.5   | 10    | 2     |
| Clutch lever bracket            | 10     | 7.5   |       |
| Connecting rod (front & rear)   | 60.7   | 45    | 2     |
| Cover bolt                      | 6.7    | 5     |       |
| Disc cover bolts (front)        | 6.7    | 5     | 3     |
| Drive sprocket bolts            | 35     | 26    | 2     |
| Engine mount (upper)            | 54     | 40    | 2     |
| Engine mounting bolt (bottom)   | 51.3   | 38    | 3     |
| Exhaust joint clamp             | 24.4   | 18    |       |
| Fender bolts (front * rear)     | 6.7    | 5     | 3     |
| Fork guard bolts                | 6.7    | 5     | 3     |
| Handlebar riser (lower)         | 37.8   | 28    | 2     |
| Handlebar riser (upper)         | 27     | 20    | 3     |
| Kick stand bolt                 | 40.5   | 30    | 3     |
| Linkage connection              | 64.8   | 48    | 2     |
| Master cylinder bracket (front) | 10     | 7.5   |       |
| Rim lock nut                    | 13.5   | 10    | 2     |
| Seat bolts                      | 24.4   | 18    | 3     |
| Shock absorber nut (top)        | 47.4   | 35    | 3     |
| Shock mount (lower)             | 48.6   | 36    | 1     |
| Shock spring lock nut           | 46     | 34    |       |
| Shroud bolts                    | 4.7    | 3.5   |       |
| Silencer mount bolt             | 24.4   | 18    | 3     |
| Steering stem nut               | 101    | 75    |       |
| Sub-frame bolt (lower)          | 33.8   | 25    | 2     |
| Sub-frame bolt (upper)          | 29.8   | 22    |       |
| Triple clamp (lower & upper)    | 21     | 15    | 2     |

Notes: 1. Apply oil to threads 2. Apply lock-tite liquid to threads (Red) (Use sparingly)  
3. Apply lock-tite liquid to threads (Blue)

